

# Radiant Dyes Laser Acc. GmbH

## Optics

### For Dye Laser

For our Dye Laser we offer only our standard optics which are included in the laser.

- \* Pump optics for all existing dye lasers  
Pump optic-set: 308 nm, 355 nm or 532 nm

### CW-Dye-Laser

- \* Optic-Set for self-made dye ring laser and Coherent 699  
-> Optic-Set VIS , P1, M1, M4, M5 & Tweeter
- \* Optic-Set for self-made dye ring laser and Coherent 699  
-> Optic-Set BLUE (without Tweeter), P1, M1, M4, M5 & Tweeter
- \* Optic-Set for self-made TiSa laser and Coherent 899  
-> Optic-Set TiSa (without Tweeter), P1, P2, P3, M1, M4, M5 & Tweeter

### Excimer-Laser

- \* (0° an 45°) and -windows:  
Material: MgF2 or CaF2  
Diameter, thickness : 36mm or 38mm (1,5"), d= 5mm  
Mirrorcoating: Al or dielectric @ 193, 248, 308 nm



Radiant Dyes Laser & Acc. GmbH,  
Friedrichstr. 58, 42929 Wermelskirchen, Germany  
Tel: 0049 (0)2196-81061, Fax: 0049 (0)2196-3422  
<http://www.radiant-dyes.com>, E-mail: [info@radiant-dyes.com](mailto:info@radiant-dyes.com)

